



View of upper floor runs

### The Double-D™ Double Deck Advantage:

- Add runs without adding on to your building
- Boosts kennel capacity without cutting corners on quality
- Able to adapt to nearly any building layout

*"Therian installed our first Mason kennel system in 2003. We were so impressed with the quality of the Mason Double-D system; we have since installed a Chainlink Sani-Kennel system and the Mason luxury dog and cat suites."*

P Connors, Hanrob The Ultimate Pet Destination, Heathcote NSW

## Add Up the Savings to Building Up!



Need room to grow however limited on space? Just look up... to Mason's Double-D™ Modular Double Deck Kennels the ultimate space problem-solver! Our exclusive design allows you to add more runs without adding on to your building. All patented Double-D™ runs are full height and provide easy walk-in access for dogs and handlers. Maximise your revenue producing capacity without compromising quality.

Engineered for flexibility, Double-D™ Kennels can conform to a wide range of building dimensions, making it possible to install double deck runs in rooms as narrow as 4267mm with only 3657mm of interior head room. The Double-D™ comes with a complete plumbing and drainage system for the upper level and aisles. Stairways provided by others can be positioned in a variety of locations.

Choose from our Back-to-Back or Single-Row Double-D™ System. Double-D™ runs are available with stainless steel, chainlink, or our new galvanised welded wire gates, along with optional swing-up rest benches.

*Refer to reverse for unit details and options.*

**FREECALL 1800 251 766**

# Double-D™ Kennels

Unit details & options (Refer to Specifications Insert for further details)

## Building Requirements

- Height: 4268mm (standard), 3660mm (low headroom)
- Width: 3660mm minimum for single row system  
6100mm minimum for standard back-to-back system
- Drainage: 305mm - wide building-floor trench drain

## Available Sizes

### First-Floor Run

- Length: 1830mm - 3048mm
- Width: 610mm, 1220mm, 1830mm, 2134mm and 2440mm

### Upper-Level Run

- Length: 1220mm - 2440mm (depending on lower level)
- Width: 915mm - 1220mm
- Upper Aisle Width: 1220mm
- Typical Stairway Units Width: 1220mm (to be provided by other)

## Standard Features

### First-Floor Run

- Mason Kenl-Dor® on common back panels

### Upper-Level Run

- UltraBase with built-in floor drain

## Options

- Refer to Doors & Accessories Insert for details
- Swing-up rest bench



## Gates and Stall Fronts

All of Mason's gates and stall fronts come pre-hung and completely assembled. Standard inclusions: Single bowl insert with 1 x stainless steel bowl plus and Double bowl insert with 2 x stainless steel bowls.

### Stainless Steel Gates

#### Available Sizes

- Height: 1880mm \*
- Width: 610mm - 915mm \*

### Stainless Steel Stall Fronts

#### Available Sizes

- Height: 1880mm \*
- Width: 915mm - 2440mm \*

### Frame, Grid and Panel

#### Mounting Frame:

- 6061-T6 aluminium solid bar

#### Gate Grid:

- 304 stainless steel wire
- Vertical 38mm diameter
- Horizontal 6mm diameter


#### Optional Solid Section:

- Tempered glass
- FRP
- Other sheet materials


\*Call for additional size availability.




Stainless Steel Swing Gate




Stainless Steel Stall Front



Glass over Stainless Combo Stall Front



Glass Gate



Glass Stall Front

### Galvanised Welded Wire Gates

**NEW!**

#### Available Sizes

- Height: 1880mm \*
- Width: 610mm - 915mm \*

### Galvanised Welded Wire Stall Fronts

#### Available Sizes

- Height: 1880mm \*
- Width: 915mm - 2440mm \*

\*Call for additional size availability.

### Frame, Grid and Panel

#### Mounting Frame


- 1x16 gauge (.065 wall)
- Square HRPO ASTM A513 tubing

#### Gate Grid


- Cold rolled steel wire
- Vertical 3mm diameter
- Horizontal 6mm diameter

#### Optional Solid Section

- Tempered glass
- FRP
- Other sheet materials



Galvanised Welded Wire Swing Gate



Galvanised Welded Wire Stall Front

### Chainlink Swing Gates

With Never-Fail Latch

#### Available Sizes

- Height: 610mm - 2440mm
- Width: 610mm - 1220mm

#### Options

- 1880mm high entry frame
- Fixed bottom panel
- Dutch doors

### Chainlink Stall Fronts


Required for runs that exceed 1220mm in width.

#### Available Sizes


- Height: 915mm - 2440mm
- Width: 915mm - 3660mm

#### Options

- All Swing Gate options
- Gate location at other end
- See Chainlink Sani-Kennel for other gate options



Chainlink Gate



Chainlink Stall Front

## Top Covers

Dogs stay safe and secure with Mason's top covers. Refer to the Doors & Accessories insert for details.

## Rest Benches

Swing-up rest benches keep dogs away from the rear gutter and permit easy cleaning. Refer to the Doors & Accessories insert for details.